



## Technical Data Sheet

### Zwaluw® Acryl Wet on Wet Instant paintable acrylic sealant



#### Product Description

Zwaluw Acryl Wet on Wet is a high quality acrylic sealant especially developed to be overpainted wet-in-wet with water based and synthetic paints, shortly after application. For sealing and filling of connection joints, seams, chinks and cracks.

#### Benefits

- Wet on wet paintable, shortly after application, with waterbased and synthetic paints.
- No discoloration of paint.
- Minimal risk of cracking.
- Perfect adhesion without the use of a primer, even on slightly damp substrates.
- Nearly non smelling.
- Easy to apply and clean.
- Not corrosive on metals.

#### Applications

Zwaluw Acryl Wet on Wet has been especially developed for sealing interior connection joints between stairs, walls, ceilings, skirting boards, windowsills, concrete and brickwork. For filling cracks, screw- and nail holes in walls and ceilings of wood, plastering, gypsum, brickwork, concrete etc.

#### Additional information

100% Modulus		0,52 MPa
Application Rate		100 g/min @ 3mm/4 bar
Application Temperature		+5°C - +40°C
Base		Akrična disperzija
Curing Time		1mm / dan
Density		0,71 g/ml
Elongation at Break		132%
Fire Rating		Class E
Flow		1 mm
Frost Resistance during transportation		Do -15°C
Shore-A hardness	DIN 53505	33 Shore A
Skin Formation		2min @ 23°C/55% RH
Temperature Resistance		-20°C till +75°C
Tensile Strength (DIN 53504)		0,52 MPa

#### Limitations

- Not suitable for continuous water load
- Not suitable for PE, PP, PC, PMMA, PTFE, neoprene and bituminous substrates

#### Surface Preparations and Finishing

Application temperature +5°C till +40°C (applies to environment and substrate). All surfaces must be clean, dry and free from dust, grease and solid substrate. Substrate to be cleaned from all loose particles, porous substrate do not require to be absolutely dry. Very porous substrates like: gypsum, aerated concrete, limestone, etc, need to be primed with a mixture of 1 part Zwaluw Acryl Wet on Wet and 2 parts water. Adhesion tests prior to application are recommended. Finish and smoothen with water.

#### Paintability





## Technical Data Sheet

### Zwaluw® Acryl Wet on Wet

#### Instant paintable acrylic sealant

Zwaluw Acryl Wet on Wet is paintable shortly after application with water based and synthetic paints at small joints. At wider joints cracking in paint by shrinkage of sealant can occur. It is recommended to test compatibility with paint prior to application.

or transport and therefore we do not accept any liability for damage. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.

#### Cleaning

Tools to be cleaned after use with water. Hands can be cleaned with Zwaluw Wipes and/or water and soap.

#### Colour(s)

- White


#### Packaging

- Cartridge 310 ml

#### Shelf Life

in unopened original packaging between +5°C and +25°C, shelf life till 12 months after production date, stored in a dry place

#### Certifications

	EN 15651-1: F-INT
--	-------------------

#### Health & Safety

Product Health and Safety Data Sheet must be read and understood before use. These are available on request and via the Den Braven websites.

#### Warranty & Guarantee

Den Braven warrants that its product complies, within its shelf life, to its specification.

#### Disclaimer

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Den Braven. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Den Braven's written consent. The technical information in this document serves as an indication and is non-exhaustive. Den Braven is not liable for any damage, either direct or indirect, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Den Braven reserves the right to amend the wording of this document. Den Braven cannot be held liable for any damage, either direct or indirect, due to the use of the product depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage

